

# Tekno

With horizontal and customizable sectors, a concentrate of innovation and technology that perfectly matches the solutions of modern architectural projects

## The door with concealed hinges:

- 100° Opening
- Maximum feasible measures 1300x3000mm single leaf  
1900x3000mm double leaf
- Other measurements on request
- Door profiles and frame cover in brushed aluminum  
standard supplied steel without visible screws
- Motorized electronic lock with integrated access control  
system on request



# Tekno specifications

Safety door Tekno, flush with internal wall/coplanar with surrounding frame: leaf in 15/10 electro-galvanized sheet steel with 3 horizontal reinforcing bars and 2 vertical reinforcing bars, 30/10 lock protection plate, closing profiles and frame covering profiles in aluminum in 5 finishes, perimeter frame sealing strip, internal insulation, draught excluder, brushed chrome square internal/external kit, closed sector frame, 2 patented concealed hinges, 2 side switchlocks, cylinder lock with defender included.



- 1 Leaf tray
- 2 Horizontal reinforcing bar
- 3 Vertical reinforcing bar
- 4 Cylinder lock
- 5 Lock protection and support plate
- 6 Lock connecting rods with closure points
- 7 Switchlock
- 8 Concealed hinge
- 9 Draught excluder
- 10 Insulation
- 11 Heat barrier mat
- 12 Tubular rubber sealing strip
- 13 Aluminum frame profiles
- 14 Closed hollow frame
- 15 Internal covering panel
- 16 Satin chrome handle kit
- 17 Defender satin chrome

